

11301-G/D Smart Gauge/Differential Pressure Transmitter

GENERAL

11301 series is a digital differential pressure transmitter designed for industrial pressure measurement applications.

The 11301 can be configured to provide integrated solutions for a broad range of pressure and flow measurement applications.

FEATURES

- ❑ Updating time of output current in 200 ms
- ❑ Improved performance, increased accuracy and greater stability
- ❑ Two years stability of 0.2%
- ❑ 0.1% accuracy
- ❑ Parameter setting by keypad directly
- ❑ 4-20 mA output plus direct digital HART communication
- ❑ Automatic zero calibration by press-button
- ❑ Explosion proof and weather proof housing

STANDARD SPECIFICATION


- Process Fluid: Liquid, Gas or Vapor
- Application: Gauge Pressure, Differential Pressure
- Measuring Range:
0 - 0.125 KPa ~ 0 - 1.5 KPa (Minimum)
0 - 1170 KPa ~ 0 - 6890 KPa (Maximum)
- Accuracy : 0.1% of span
- Stability: +/- 0.2% of URL for 2 years
- Working Temperature : -25 to +95 °C
- Max. Pressure : 25 MPa
- Material:
Flange/Adapter: Stainless Steel 304 / Stainless Steel 316
Drains/Vents: Stainless Steel 304 / Stainless Steel 316
Diaphragm: Stainless Steel 316L / Hastelloy B / Hastelloy C / Monel / Tantalum
Wetted O-Ring : Buna N / Viton / PTFE
Bolts & Nuts : Carbon Steel / Stainless Steel 316
Mounting Bracket : Carbon steel / Stainless Steel 304 / 316
Name / Tag Plate : Stainless Steel 304 / Stainless Steel 316
Converter Housing : Low copper cast aluminum alloy with polyurethane paint
Fill Fluid : Silicone / Fluorolube Oil
- Protection Class: IP65 (Standard)
Intrinsically Safe EEx ia IIC T5 (Standard)
Explosion proof Ex D IIB T5
- Display : 5 Digits programmable & 0-100% Bargraph
- Display Unit:
Standard 22 different engineering unit
5 Digits programmable for special unit
- Keypad : 3 internal keys for programming and output setting
- Current Output : 4 - 20 mA 2 wires with Hart signal
Load: Rohm = (Vdc-9)*50
- Power Supply : 9 - 36 VDC
- Damping : 0 - 32 seconds
- Response Time : 200 mS
- Mounting : Bracket on 2" Pipe
- Humidity Limit : 0 to 100% Relative Humidity
- Turn on Time : 2 Seconds with minimum damping
- Zero Calibration : Automatic zero calibration by press-button
- Cable Entry : M20 Conduit Threads / 1/2" NPT (Female)
- Temperature Effect : +/-0.18% ~ +/-0.5% of span per 20 °C
- Vibration Effect : +/-0.05% of URL per g to 200 Hz in any axis
- EMI/RFI Effect : Follow SAMA PMC 33.1 from 20 to 1000MHz and for field strengths up to 30 V/m
- Process Connection:
1/4" - 18 NPT
1/2" - 14 NPT(with adapter)
- Ambient Temperature : -25 to +80 °C
- Dimensions : 102 mm (W) * 188 mm (H) * 130 mm (D)
- Weight : 3.5 Kg




MEASURING RANGE

Range Code	Range Limits		Transmitter type	
	Min. Span	Max. Span	Differential Pressure	Gauge Pressure
2	0 ~ 0.125 KPa	0 ~ 1.5 KPa	◆	◆
	0 ~ 12.7 mmH2O	0 ~ 153 mmH2O		
	0 ~ 13 mbar	0 ~ 75 mbar		
3	0 ~ 1.3 KPa	0 ~ 7.5 KPa	◆	◆
	0 ~ 132.6 mmH2O	0 ~ 764.8 mmH2O		
	0 ~ 13 mbar	0 ~ 75 mbar		
4	0 ~ 6.2 KPa	0 ~ 37.4 KPa	◆	◆
	0 ~ 632.2 mmH2O	0 ~ 3813.7 mmH2O		
	0 ~ 62 mbar	0 ~ 374 mbar		
5	0 ~ 31 KPa	0 ~ 186.8 KPa	◆	◆
	0 ~ 3161 mmH2O	0 ~ 19048 mmH2O		
	0 ~ 310 mbar	0 ~ 1868 mbar		
6	0 ~ 117 KPa	0 ~ 690 KPa	◆	◆
	0 ~ 11930 mmH2O	0 ~ 70360 mmH2O		
	0 ~ 1170 mbar	0 ~ 6900 mbar		
7	0 ~ 345 KPa	0 ~ 2068 KPa	◆	◆
	0 ~ 35.18 mH2O	0 ~ 210.9 mH2O		
	0 ~ 3.45 bar	0 ~ 20.68 bar		
8	0 ~ 1170 KPa	0 ~ 6890 KPa		◆
	0 ~ 119.3 mH2O	0 ~ 702.6 mH2O		
	0 ~ 11.7 bar	0 ~ 68.9 bar		


WIRING DIAGRAM



➤ DIMENSIONS



➤ Supply Voltage VS Loop Load



MODEL SELECTION GUIDE

Item	Code	Specification
11301-D		Differential Pressure Transmitter (Range 2 to 7)
11301-G		Gauge Pressure Transmitter (Range 2 to 8)
Measurement Range	2	0 ~ 1,5 Kpa
	3	0 ~ 7,5 Kpa
	4	0 ~ 37,4 Kpa
	5	0 ~ 186,8 Kpa
	6	0 ~ 690 Kpa
	7	0 ~ 2068 Kpa
	8	0 ~ 6890 Kpa
Output	S	4-20mA + HART Protocol, Linear output (¹)
Diaphragm Material / Fill Fluid	2	Stainless Steel 316L Silicone Oil
	3	Hastelloy C (Range > 3 Kpa)
	A	Stainless Steel 316L Fluorine Oil
Drain hole	B	Back of process flange or none
	U	Process flange side upper
	L	Process flange side lower
Wetted O-ring Material	7	Buna-N (NBR)
	6	Viton (FKM) (Temperature ≥ -20°C)
	5	Low Temperature Viton (FKM-GFLT)
Process Connection	H	1/4" NPT F
Maximum Pressure Limit	1	14 Mpa (4 Mpa for range 2)
	3	25 Mpa
Cable Entry	1	M20 x 1.5
	2	1/2 NPT
Mounting Bracket	B00	None
	B01	Tube-type Curved Bracket (carbon steel)
	B02	Wall mounting bracket (carbon steel)
	B03	Tube-type Flat Bracket (carbon steel)
	B04	Tube-type Curved Bracket (stainless steel)
	B05	Wall mounting bracket (stainless steel)
	B06	Tube-type Flat Bracket (stainless steel)
Optional	M3	LCD Display
	D1	Stainless steel drain valve or screw (2pcs)
	C1	1/2" NPT female waist flange (2sets)
	C12	1/2" NPT-M20x1.5-Ø14 pressure pipe (2sets)
	C2	M20 x 1.5 male thread T joint (2sets)
	C21	M20 x 1.5 T joint - Ø14 pressure pipe (2sets)
	d	Intrinsically safe type, Flameproof (Exd IIC T4~T6)
	i	Intrinsically safe (Exia IIC T4~T6)
	K1	Degreasing treatment

¹ Square root output (Range ≥ 5Kpa)



Fertron reserves the right to make changes to the design and functionality of any product without notice. Fertron is not responsible for the improper use or application of no product. Our logo is a registered trademark of Fertron. HART is a brand registered with the HART Communication Foundation. © 2016 Fertron. All the rights reserved.

*Fertron Automação Industrial Ltda
Av. César Mingossi, 108 • Jardim das Palmeiras, Sertãozinho SP, Brazil 14177-000
Tel: +55 (16) 3946.5899 • vendas@fertron.com.br •
www.fertron.com.br*